# **Silver Combination**

TECHNICAL SPECIFICATIONS	
Drain	End drain
Pump Location(s): Select 2	Std. = Standard / Alt LF/RF Optional
Bath Weight (empty)	175 lbs
Gallons to Operate	48-67

ELECTRICAL SPECIFICATIONS	
Motor/Pump	(2) 115v 20AMP GFCI Circuits
Inline Stainless Steel Heater	(Opt.) 115v 20AMP GFCI Circuit

BATHERS: 1		
INSTALLATION		
	DECK (D)	
	UNDER MOUNT (U)	
•	ALCOVE (A)	
	FREESTANDING (F)	
	CLAWFOOT (L)	
	PEDESTAL (P)	





# STANDARD FEATURES & ACCESSORIES for SILVER COMBINATION

21 Air & Water Massage Jets Accumassage Back, Neck Jets Ultra Flow Jets - 6-Micro Flow Jets (•) Classic Air Jets O

SKU: MYSTIQUE6SKTF-SCB

### **PUMPS**

2.25 Hydropower 1-speed Pump 1.0 Air Power 3-Speed Warm Air Pump Quiet Pad Anti-Vibration Mounted Pump

#### **CONTROLS**

Air Switch On/Off Control(s) Automatic Purge & Dry Cycle Control

# **PURITY**

HydroClean Water Purity System HydroCleanse

#### STANDARD ACCESSORIES

Mood Light

Lift & Turn Drain - White, Biscuit, Bone, Brushed Nickel, Oil Rubbed Bronze, Polished Chrome

Deluxe Cushion Pillow Integral Tile Flange

EZ Level Adjustable Legs

FDA Recipe Non-Toxic Food & Beverage Grade Plumbing (primarily)

30 Point Quality Assurance Factory Test

# **REQUIREMENTS**

Pump Locations: Select 2

Electrical: two 115v 20amp GFCI Circuits

Tub should not be supported by the lip in any way. Leve

tub & screw or glue EZ Level adjustable legs to sub floor.

**CUT OUT DIMENSIONS:** 


**OVALS:** A template will be provided

**RECTANGLES:** Subtract 1" to 1.5" from length & width for hole

cut out size

**EZ CLEAN CAST ACRYLIC** LIMITED LIFETIME WARRANTY (UL) us ANSI





NOTE: Graphics may not be to scale. Specifications and features are subject to change without notice and are ± .25". All final measurements should be taken from tub on site. Access 18"x 18" or larger is required for each pump. Some pump locations and plumbing may extend beyond the perimeter of the bath.