Serenity 7 Silver Water Jet 87"x36" x 21"

PRODUCT NUMBER: SERENITY7-SWJ



SILVER WATER JET

TECHNICAL SPECIFICATIONS				
Drain	End drain			
Pump Location(s): Select 1	Std. = Standard / Alt LF/RF Optional			
Bath Weight (empty)	180 lbs			
Gallons to Operate	58-76			
ELECTRICAL SPECIFICATIONS				

		INGIALLATION	
Std. = Standard / Alt LF/RF Optional		•	DECK (D)
180 lbs			UNDER MOUNT (U)
58-76		•	ALCOVE (A)
NS			FREESTANDING (F)
(1) 115v 20AMP GFCI Circuits			CLAWFOOT (L)
(Opt) 115v 20AMP GFCI Circuit			PEDESTAL (P)

BATHERS: 1

Jet & Control placement may vary



STANDARD FEATURES & ACCESSORIES for SILVER WATER JET

JETS

Motor/Pump

9 Water Jets Tri-Zone Back Systems 3 Jets Ultra Flow Jets -

Inline Stainless Steel Heater

PUMPS

2.25 Hydropower 1-speed Pump Quiet Pad Anti-Vibration Mounted Pump

CONTROLS

Micro Flow Jets (•)

Air Switch On/Off Control(s)

PURITY

HydroClean Water Purity System HydroCleanse

STANDARD ACCESSORIES

FDA Recipe Non-Tok c Food & Beverage Grade Plumbing (primarily) 30 Point Quality Assurance Factory Test EZ Level Adjustable Legs

COLOR

Only Available in White

REQUIREMENTS

Pump Locations: Select 1

Electrical: one 115v 20AMP GFCI Circuits

Tub should not be supported by the lip in any way.

Level tub & screw or glue EZ Level adjustable legs to sub floor. **CUT OUT DIMENSIONS:**

OVALS: A template will be provided


RECTANGLES: Subtract 1" to 1.5" from length & width for hole


cut out siæ

EZ CLEAN CAST ACRYLIC LIMITED LIFETIME WARRANTY C(UL)us ANSI












INSTALLATION WILL NOT REQUIRE MORTAR BEDDING







Some standard & most alternate pump locations may stickout past perimeter of the bath 1"-3". NOTE: Graphics may not be to scale. Specifications and features are subject to change without notice and are ± .25". All final measurements should be taken from tub on site.

Access 18"x 18" or larger is required for each pump. Consult your contractor for installation requirements.