♣ 🏻 SKU: ZEN534SKTF-GWJ

TECHNICAL SPECIFICATIONS	
Drain	End drain
Pump Location(s): Select 1	Std. = Standard / Alt LF/RF Optional
Bath Weight (empty)	165 lbs
Gallons to Operate	38-56

ELECTRICAL SPECIFICATIONS	
Motor/Pump	(1) 115v 20AMP GFCI Circuits
Inline Stainless Steel Heater	(1) 115v 20AMP GFCI Circuit

STANDARD FEATURES & ACCESSORIES for GOLD WATER JET

12 Water Massage Jets Back Massage System(s) (6 Jets) Accumassage Back and Neck Jets 6 Ultra Flow Jets - ()-

PUMPS

3.25 Hydropower 3-speed Pump Quiet Pad Anti-Vibration Mounted Pump

HEATERS

Stainless Steel Electric Heater

CONTROLS

Air Switch On/Off Control(s) For Hydro Pump & Mood Light 3 Speed Massage: High, Medium or Low

PURITY

HydroClean Water Purity System HydroCleanse







Gold Water Jet

STANDARD ACCESSORIES

Mood Light

Lift & Turn Drain - White, Biscuit, Bone, Brushed Nickel, Oil Rubbed Bronze, Polished Chrome

Deluxe Cushion Pillow

Integral Skirt with Magnetic Access Panel

EZ Level Adjustable Legs

FDA Recipe Non-Toxic Food & Beverage Grade Plumbing (primarily) 30 Point Quality Assurance Factory Test

REQUIREMENTS

Pump Locations: Select 1 Electrical: two 115v GFCI Circuits Drain: Select Color / Finish

Tub should not be supported by the lip in any way.

Level tub & screw or glue adjustable legs to sub floor. **CUT OUT DIMENSIONS:**


OVALS: A template will be provided

RECTANGLES: Subtract 1" to 1.5" from length & width for hole


cut out size


EZ CLEAN CAST ACRYLIC LIMITED LIFETIME WARRANTY CULUS ANSI






Bath includes EZ Level Legs **INSTALLATION WILL NOT REQUIRE MORTAR BEDDING**







Backrest angle

NOTE: Graphics may not be to scale. Specifications and features are subject to change without notice and are ± .25". All final measurements should be taken from tub on site. Access 18"x 18" or larger is required for each pump. Some pump locations and plumbing may extend beyond the perimeter of the bath.