SKU: ECLIPSE-5-SWJ

SII	_VER	WΔ.	TFR	.IFT

TECHNICAL SPECIFICATIONS				
Drain	End drain			
Pump Location(s): Select 1	Std. = Standard / Alt LF/RF Optional			
Bath Weight (empty)	140 lbs			
Gallons to Operate	42-60			
ELECTRICAL SPECIFICATIONS				
Motor/Pump	(1) 115v 20AMP GFCI Circuits			
Inline Stainless Steel Heater	(Opt) 115v 20AMP GFCI Circuit			

BATHERS: 1			
INSTALLATION			
•	DECK (D)		
	UNDER MOUNT (U)		
	ALCOVE (A)		
	FREESTANDING (F)		
	CLAWFOOT (L)		
	PEDESTAL (P)		



STANDARD FEATURES & ACCESSORIES for SILVER WATER JET

JETS

9 Water Jets Tri-Zone Back Systems 3 Jets Ultra Flow Jets - - -Micro Flow Jets (•)

PUMPS

2.25 Hydropower 1-speed Pump Quiet Pad Anti-Vibration Mounted Pump

CONTROLS

Air Switch On/Off Control(s)

PURITY

HydroClean Water Purity System HydroCleanse

STANDARD ACCESSORIES

FDA Recipe Non-Toxic Food & Beverage Grade Plumbing (primarily) 30 Point Quality Assurance Factory Test EZ Level Adjustable Legs

REQUIREMENTS

Pump Locations: Select 1

Electrical: one 115v 20AMP GFCI Circuits

Tub should not be supported by the lip in any way.

Level tub & screw or glue EZ Level adjustable legs to sub floor. **CUT OUT DIMENSIONS:**

OVALS: A template will be provided


RECTANGLES: Subtract 1" to 1.5" from length & width for hole


cut out size

EZ CLEAN CAST ACRYLIC LIMITED LIFETIME WARRANTY












INSTALLATION WILL NOT REQUIRE MORTAR BEDDING







Some standard & most alternate pump locations may stickout past perimeter of the bath 1"-3". NOTE: Graphics may not be to scale. Specifications and features are subject to change without notice and are ± .25". All final measurements should be taken from tub on site.

Access 18"x 18" or larger is required for each pump. Consult your contractor for installation requirements.